

HF-100® / Grip Kit Tutorial

STEP 1 – Removing Old Grip and Tape

- Secure the club in a vise using the rubber vise clamp.
- Remove the grip using a razor knife with hooked blade.
- Strip off the old tape. We recommend using the Uneekscraper.



HF-100® / Grip Kit Tutorial

STEP 2 – Taping the Shaft

- Measure a length of tape equal to the length of the grip.
- If using pre-cut tape strips, remove scored liner first.
Note: this step is only required when using tape strips.
- Apply the adhesive side to the shaft ½” beyond the end of the club and wrap the tape strip around the entire length of the shaft.
- Remove the outside liner off the tape. Then, twist and push the ½” extended tape into the open end of the shaft.



HF-100® / Grip Kit Tutorial

STEP 3 – Applying HF-100

- Spray HF-100 on the entire length of the tape (just enough to wet the tape).
- Spray a small amount of solution into the grip and pour the remainder over the tape.



HF-100® / Grip Kit Tutorial

STEP 4 – Installing the New Grip

- Install the grip by pushing it over the tape.
- Make sure the grip and club face are in proper alignment.
- Remove the club from the vise. Wipe any excess solution with a towel and gently tap the end of the grip on the ground to force out any trapped solution. Let dry for 20 minutes.

