Brampton Technology, Ltd 167 South St. West Hartford, CT 06110

860-667-7689

Brampton PRO-FIX® Glass Beads 1/24/2023

Chemical Names	CASNo.	Percent*			
			Evnogues I imits in Air (sixo		
Silica	60676-86-0	>67%	Exposure Limits in Air (give units)		
			ACGIH TLV		
Aluminum Oxide	1344028-1	<1%	OSHA PEL OTHER (specify)		
Potassium Oxide	12136-45-7	<7%	8 Hr. TWA 10mg/m3		
Boric Oxide	1303-86-2	<2%	Nuisance particulate)		
Barium Oxide	1304-28-5	<6%	0.3 mg/m ³ Total mass		
Lime	1305-78-8	<5%	g		
Soda Magnasium Ovida	1313-59-3	<10%	Material contains		
Magnesium Oxide	1309-48-4	<1%	no lead		
III. PHYSICAL PRO	DEDTIES				
		Ielting point or	range F: 900		
Vapor density:	Ingolubl B	oiling point or i	range, F: None		
Specific gravity: Solubility in	e N/A E	vaporation rate:	N/A		
water: Vapor	C 1 1/1 1	•	r: Clear Glass Beads, no odor		
water. vapor		r r			
HOW TO DETECT THIS SUBSTANCE* (WARNING PROPERTIES OF					
SUBSTANCE AS A GAS, VAPOR, DUST OR MIST)					
* Not a required category Note: All required categories should be addressed. If any item is not applicable, or no information is available, the space must be marked to indicate that. IV. FIRE & EXPLOSION					
Flash Point, F (give	method)	N/A deg. F			
Auto ignition temperature, F		N/A			
Flammable limits in air, volume% N/A - lower (LEL) N/A upper (UEL) N/A					
Fire extinguishing materials		N/A			
water spray carbon dioxide other foam dry chemical					
Special firefighting procedure: None Unusual fire and explosion hazards: None					
V. HEALTH HAZARD INFORMATION					
SYMPTOMS OF OVEREXPOSURE for each potential route of exposure					
Inhaled: Fired or sintered soda lime glass has no known health hazard.					

Inhaled: Fired or sintered soda lime glass has no known health hazard.

Avoid breathing dust, and keep out of eyes.

Contact with skin or eyes: Little hazard exists, other than possible irritation.

Absorbed through skin: Not likely

Swallowed: From information available little hazard exists, however, may cause irritation.

HEALTH EFFECTS OR RISKS FROM EXPOSURE

Acute: This is a non-toxic material with a free silica (quartz) content of less than 1.0% and TLV of a nuisance p articulate.

Chronic:				
FIRST AID - EMERGENCY PROCEDURES				
-	lenty of water. ghly with soap and water ention			
SUSPECTED CANCER AGENT:	:			
XX NO: This product's ingredien	nts are not found in the he list below:			
YES: XX Federal OSHA XX NPT XX IARC				
California employers using Cal/O The Cal/OSHA and Federal OSH.	SHA - regulated carcinogens must register with Cal/OSHA. A carcinogen list are similar.			
MEDICAL CONDITIONS AGGRAVA	TED BY EXPOSURE: NONE			
VI. REACTIVITY DATA				
Stability: XX Stable Un Conditions to avoid:	nstable			
Incompatibility (material to avoid): Hydrofluoric acid attacks glass				
Hazardous decomposition products (including combustion products): N/A				
Hazardous polymerization:May occurX_ Will not occur				
VII. SPILL, LEAK AND DISPOSAL PROCEDURES				
Spill response procedures (include employee prote	ection measures).			
Collect in a convenient manner, which will avoid dusting. No special precautions required.				
Page 3 Brampton Glass Beads				
Preparing wastes for disposal (container types, neutralization, etc).				
Dispose of the material as an inert solid in a land-fill.				
NOTE: Dispose of all wastes in accordance with federal, state and local regulations. VIII. SPECIAL HANDLING INFORMATION				
Ventilation and engineering controls:	Exhaust to maintain levels below PEL			
Respiratory protection (type):	NIOSH/MSHA approved dust and/or fume respirator			
Eye protection (type):	Safety glasses or goggles			
Gloves (specify material):	Recommended/latex			

Full body cover may be desirable with heavy dusting.

Other clothing and equipment: